

Christie Boxer 4K30

Christie Boxer 4K30 144-001012-02		
Immagine	luminosità	<ul style="list-style-type: none"> • 29,000 ANSI (standard) • 30,000 Center • 32,500 ISO
	contrasto	• 2000:1
Tecnologia display	tipo	• 3DLP® 1.38" DMD
	risoluzione nativa	• 4K (4096 x 2160)
Lampada	tipo	• 6 x 450W NSH
	durata	• 1500 ore a 70% della luminosità iniziale
Ingressi		<ul style="list-style-type: none"> • 2 x Dual 3G HD-SDI input card • 2 x Twin DisplayPort input card • HDBaseT
Pixel clock		• 1.2Gpx/s - Christie® TruLife Electronics
Networking		<ul style="list-style-type: none"> • Tastiera • RS232 in • Ethernet (10/100) RJ45
Montatura obiettivi		<ul style="list-style-type: none"> • Sistema inserimento lenti senza attrezzi • Vista foro regolabile • Offset lente orizzontale e verticale motorizzato • Zoom motorizzato e messa a fuoco
Obiettivi	fissi	<ul style="list-style-type: none"> • 0.72:1 (no offset) • 0.9:1 (offset: V: ±45%, H: ±15%)
	zoom	<ul style="list-style-type: none"> • 1.13-1.31:1 (offset: V: ±60%, H: 25%) • 1.31-1.63:1 (offset: V: ±80%, H: 30%) • 1.63-2.17:1 (offset: V: ±80%, H: 30%) • 1.99-2.71:1 (offset: V: ±15%, H: 5%) • 2.71-3.89:1 (offset: V: ±45%, H: 15%) • 3.89-5.43:1 (offset: V: ±85%, H: 25%) • 4.96-1-7.69:1 (offset: V: ±55%, H: 20%)
Accessori opzionali		<ul style="list-style-type: none"> • Dual link DVI input card • Twin HDMI™ input card • Dual 3G HD-SDI input card • Twin DisplayPort input card • Telaio per manovra e impilamento • HB multi input card • Quad DisplayPort input card (HB)
Requisiti alimentazione	voltaggio funzionamento	• 200-240V
	corrente funzionamento	• 19A
Dimensioni	dimensioni	• (LxWxH): 37.75 x 23.5 x 12" (959 x 597 x 305mm)
	peso	• 160lbs (72.57kg)
Ambiente operativo	temperatura	• 41-104°F (5 to 40°C)
	umidità	• 10-80%, non-condensing
Garanzia		• Tre anni

Per le specifiche relative a Christie Boxer 2K20, 2K25 e 2K30, visitare christieemea.com

Independent Sales Consultant Office

Italy
Independent Sales Consultant Office
Angelo Tacca
AT Consulting Immobiliare S.r.l.
Via Primo Maggio, 18
20024 Garbagnate Milanese (MI)
Italy
PH: +39 (0) 2 9902 1161

EMEA offices

United Kingdom
EMEA Regional Head Office
PH: +44 (0) 118 977 8000

Africa
PH: +27 71 335 8667

Eastern Europe
Representative Office
PH: +36 (0)1 47 48 138

France
PH: +33 (0) 1 41 21 44 04

Germany
PH: +49 2161 566 200

Middle East
PH: +971 (4) 503 6800

Spain
PH: +34 91 633 9990

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961



Per informazioni più aggiornate sulle specifiche, si prega di visitare www.christieemea.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
Printed in Canada on recycled paper. 4207 Jan 16

CHRISTIE®