

Christie Boxer 2K20, 2K25 and 2K30

		Christie Boxer 2K20 144-007108-01	Christie Boxer 2K25 144-008109-01	Christie Boxer 2K30 144-009100-01
Image	brightness	• 19,500 ANSI (typical) • 20,000 Center • 22,000 ISO	• 24,500 ANSI (typical) • 25,000 Center • 27,500 ISO	• 29,000 ANSI (typical) • 30,000 Center • 32,500 ISO
	contrast	• 2000:1		
Display technology	type	• 3DLP® 1.38" DMD		
	resolution	• 2K (2048 x 1080)		
Lamp	type	• 4 x 450W NSH	• 5 x 450W NSH	• 6 x 450W NSH
	life	• 1500 hrs to 70% initial brightness		
Inputs	<ul style="list-style-type: none"> • HB multi input card • HDBaseT 			
Pixel clock	• 300 Mpx/s - Christie® TruLife Lite Electronics			
Networking	<ul style="list-style-type: none"> • Keypad • RS232 in • Ethernet (10/100) RJ45 			
Lens mount	<ul style="list-style-type: none"> • Tool-free lens insertion system • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment 			
Lenses	fixed	<ul style="list-style-type: none"> • 0.72:1 (no offset) • 0.9:1 (offset: V: ±45%, H: ±15%) 		
	zoom	<ul style="list-style-type: none"> • 1.13-1.31:1 (offset: V: ±60%, H: 25%) • 1.31-1.63:1 (offset: V: ±80%, H: 30%) • 1.63-2.17:1 (offset: V: ±80%, H: 30%) • 1.99-2.71:1 (offset: V: ±15%, H: 5%) • 2.71-3.89:1 (offset: V: ±45%, H: 15%) • 3.89-5.43:1 (offset: V: ±85%, H: 25%) • 4.96:1-7.69:1 (offset: V: ±55%, H: 20%) 		
Optional accessories	<ul style="list-style-type: none"> • Dual link DVI input card • Twin HDMI™ input card • Dual 3G HD-SDI input card • Twin DisplayPort input card • Rigging and stacking frame • HB multi input card • Quad DisplayPort input card (HB) 			
Power requirements	operating voltage	• 200-240V		
	operating current	• 19A		
Dimensions	size	• (LxWxH): 37.75 x 23.5 x 12" (959 x 597 x 305mm)		
	weight	• 160lbs (72.57kg)		
Operating environment	temperature	• 41-104°F (5 to 40°C)		
	humidity	• 10-80%, non-condensing		
Warranty	• Three years			

For Christie Boxer 4K30 specs, please visit christieemea.com

United Kingdom
Branch & EMEA
Head Office
ViewPoint
200 Ashville Way
Wokingham
Berkshire, U.K.
RG41 2PL
PH: +44 (0) 118 977 8000

Middle East
Light Industrial Unit (LIU-17)
Nad Al Shibba
Sheikh Mohammed Bin Zayed Road
Dubai Silicon Oasis
PO Box: 293762
Dubai - U.A.E
PH: +971 (0) 4 503 6800

Africa
Unit C3
Northlands Deco Park
New Market Road
Northriding
Randburg
2164
Johannesburg
Gauteng
South Africa
PH: +27 71 335 8667

Other EMEA offices

Germany
Branch Office
PH: +49 2161 566 200

France
Branch Office
PH: +33 (0) 1 41 21 44 04

Eastern Europe
Representative Office
PH: +36 (0)1 47 48 138

Spain
Branch Office
PH: +34 91 633 9990

Italy
Independent Sales Consultant Office
PH: +39 (0) 2 9902 1161

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961



For the most current specification information, please visit www.christieemea.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4208 Jan 16

CHRISTIE®