

Christie Boxer 2K20, 2K25 y 2K30

		Christie Boxer 2K20 144-007108-01	Christie Boxer 2K25 144-008109-01	Christie Boxer 2K30 144-009100-01
Imagen	brillo	• 19.500 ANSI (media) • 20.000 en centro • 22.000 ISO	• 24.500 ANSI (media) • 25.000 en centro • 27.500 ISO	• 29.000 ANSI (media) • 30.000 en centro • 32.500 ISO
	contraste	• 2000:1		
Tecnología de display	tipo	• 3DLP® 1.38" DMD		
	resolución nativa	• 2K (2048 x 1080)		
Lámpara	tipo	• 4 x 450W NSH	• 5 x 450W NSH	• 6 x 450W NSH
	vida	• 1500 h. hasta llegar al 70% del brillo inicial		
Entradas	• Tarjeta de entrada múltiple HB • HDBaseT			
Reloj de píxel	• 300 Mpx/s - Christie® TruLife Lite Electronics			
Red	• Keypad • RS232 in • Ethernet (10/100) RJ45			
Montaje de lente	• Sistema de inserción de lentes sin herramientas • Referencia de alineación óptica ajustable • Offset de lente horizontal y vertical motorizado • Ajuste motorizado de objetivo y zoom			
Lentes	fija	• 0.72:1 (sin offset) • 0.9:1 (offset: V: ±45%, H: ±15%)		
	zoom	• 1.13-1.31:1 (offset: V: ±60%, H: 25%) • 1.31-1.63:1 (offset: V: ±80%, H: 30%) • 1.63-2.17:1 (offset: V: ±80%, H: 30%) • 1.99-2.71:1 (offset: V: ±15%, H: 5%) • 2.71-3.89:1 (offset: V: ±45%, H: 15%) • 3.89-5.43:1 (offset: V: ±85%, H: 25%) • 4.96:1-7.69:1 (offset: V: ±55%, H: 20%)		
Accesorios opcionales	• Tarjeta de entrada dual link DVI • Tarjeta de entrada Twin HDMI™ • Tarjeta de entrada Dual 3G HD SDI • Tarjeta de entrada Twin DisplayPort • Estructura para rigging y stacking • Tarjeta de entrada múltiple HB • Tarjeta de entrada Quad DisplayPort (HB)			
Potencia	voltaje en funcionamiento	• 200-240V		
	corriente en funcionamiento	• 19A		
Dimensiones	tamaño	• (Lg x An x Al): 37,75 x 23,5 x 12" (959 x 597 x 305mm)		
	peso	• 160lbs (72.57kg)		
Entorno de funcionamiento	temperatura	• 41-104°F (5 a 40°C)		
	humedad	• 10-80%, sin condensación		
Garantía	• Tres años			

Para información sobre las especificaciones técnicas de Christie Boxer 4K30 visite christieemea.com

Spain
P.E. Prado del Espino
c/ Labradores, Parc. 25 Nave 5
28660 Boadilla del Monte
Madrid
Spain
PH: +34 91 633 9990

EMEA offices

United Kingdom
EMEA Regional Head Office
PH: +44 (0) 118 977 8000

Africa
PH: +27 71 335 8667

Eastern Europe
Representative Office
PH: +36 (0)1 47 48 138

France
PH: +33 (0) 1 41 21 44 04

Germany
PH: +49 2161 566 200

Middle East
PH: +971 (4) 503 6800

Italy
Independent Sales Consultant Office
PH: +39 (0) 2 9902 1161

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961



For the most current specification information, please visit www.christieemea.com



Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4208 Jan 16

CHRISTIE®